

## IN THE CLAIMS

1 (Currently Amended). A method comprising:

providing current to a laser diode of an optical communication system using a transistor coupled in series with said laser diode between a power supply voltage and ground; and  
~~coupling a resistor to said transistor, said resistor parallel to said laser diode.~~  
providing a first and a second resistance, the ratio of the first to the second resistance being a matching resistance and the first and second resistances are both greater than said matching resistance.

2 (Original). The method of claim 1 including providing a differential output stage coupled to drive said transistor.

3 (Original). The method of claim 2 including providing a differential output stage coupled to gate drive said transistor.

4 (Original). The method of claim 2 including providing a differential output stage to base drive said transistor.

5 (Original). The method of claim 1 including providing an AC coupled matching resistor.

6 (Original). The method of claim 1 including providing parallel matching resistors coupled to said transistor.

7 (Currently Amended). A method comprising:

forming a direct modulation laser driver including a transistor coupled between a power supply and a laser diode;  
coupling said transistor to be driven by a differential output stage; and  
~~coupling a resistor to said transistor, parallel to said laser diode.~~

providing a first and a second resistance, the ratio of the first to the second resistance being a matching resistance and the first and second resistances are both greater than said matching resistance.

8 (Original). The method of claim 7 wherein forming a direct modulation laser driver including a transistor includes forming a driver including a field effect transistor having its gate coupled to said differential output stage.

9 (Original). The method of claim 7 wherein forming a direct modulation laser driver including a transistor includes forming a driver including a bipolar transistor having its base coupled to said differential output stage.

10 (Original). The method of claim 7 including AC coupling a shunt resistor to said transistor.

11 (Original). The method of claim 7 including providing a pair of parallel shunt resistors coupled to said transistor.

12 (Currently Amended). A driver for a direct modulation laser comprising:  
a differential output stage;  
a transistor driven by said differential output stage, said transistor coupled between a power supply and ground;  
a laser diode coupled in series with said transistor; and  
~~a resistor coupled to said transistor, in parallel to said laser diode.~~  
a first and second resistance coupled to said transistor, the ratio of the first to the second resistance being a matching resistance and the first and second resistance both being greater than the matching resistance.

13 (Original). The driver of claim 12 wherein said transistor is a field effect transistor having its gate coupled to said differential output stage.

14 (Original). The driver of claim 12 wherein said transistor is a bipolar transistor having a base coupled to said differential output stage.

15 (Original). The driver of claim 12 including a pair of parallel shunt resistors coupled to said transistor.

16 (Original). The driver of claim 12 including a shunt resistor AC coupled to said transistor.

17 (Currently Amended). A system comprising:  
a media access control; and  
a laser driver coupled to said media access control, said laser driver including a differential output stage, a transistor ~~driver~~ driven by said differential output stage, said transistor coupled between a power supply and ground, and a laser diode coupled in series with said transistor, a resistor coupled to said transistor, in parallel to said laser diode first and second resistance coupled to said transistor, the ratio of the first to the second resistance being a matching resistance and the first and second resistance both being greater than the matching resistance.

18 (Original). The system of claim 17 wherein said transistor is a field effect transistor having its gate coupled to said differential output stage.

19 (Original). The system of claim 17 wherein said transistor is a bipolar transistor having a base coupled to said differential output stage.

20 (Original). The system of claim 17 including a pair of parallel shunt resistors coupled to said transistor.

21 (Original). The system of claim 17 including a shunt resistor AC coupled to said transistor.